



- Certifications**
- cULus listed, 3hr fire-rating
  - 5 Year limited warranty

- Power Size**
- Fixed power size 1,2, 3, 4 or 5
- See selection guide for details*

- Body Material**
- Cast aluminum alloy, painted finish

- Mechanism**
- Hydraulic rack and pinion

- Fluid**
- Non-gumming, non-freezing hydraulic fluid

- Adjustments**
- Sweep speed valve
  - Latching speed valve
  - Cushioning backcheck valve – option

- Cover**
- Plastic pinion cap, painted finish

- Handing**
- Non-handed

- Opening**
- 180° maximum

- Mounting**
- Tri-Pack: regular<sup>1</sup>, top jamb<sup>1</sup>, parallel arm<sup>2</sup>
  - Maximum reveal: 3" (76mm)
  - Drop plates – available

*(1) Arm shoe allows ±7.5% power adjustment  
(2) May reduce spring power efficiency by 25%*

- Hardware**
- Wood & machine screws
  - Sex nuts & thru-bolts – available

- Available Arms**
- Regular arm

- Finish**
- AL–Aluminum, painted; BP–Brass, painted; DU–Dark bronze, painted

*Other finishes available by special order*


754	AL
MODEL	FINISH

SEE SELECTION GUIDE FOR DETAILS

## SELECTION GUIDE

MODEL	POWER SIZE	WEIGHT CAPACITY <sup>1</sup>	MAX. DOOR WIDTH <sup>2</sup>		BACKCHECK	DELAYED ACTION	FINISH	/CASE
			INTERIOR	EXTERIOR				
751	1	33–80 (15–36)	32 (813)	—	—	—	AL, BP, DU	10
752	2	55–100 (25–45)	36 (914)	—	—	—	AL, BP, DU	10
753	3	90–145 (40–66)	44 (1118)	—	—	—	AL, BP, DU	10
783					●	—	AL	10
754	4	125–190 (57–86)	48 (1219)	36 (914)	—	—	AL, BP, DU	10
784					●	—	AL, DU	10
755	5	175–265 (80–120)	52 (1321)	44 (1118)	—	—	AL, BP, DU	10
785					●	—	AL, DU	10

CAUTION: ANY DOOR CLOSER INSTALLED AND ADJUSTED BASED ON ADA REDUCED FORCE REQUIREMENTS MAY NOT RELIABLY CLOSE AND LATCH DOOR.  
 (1) WEIGHT CAPACITY RANGE IN POUNDS (KILOGRAMS) (2) MAXIMUM DOOR WIDTH IN INCHES (MILLIMETRES)



MODEL	A	B	C	D	E
751	¾ (19)	6½ (165)	1⅞ (43)	7⅞ (181)	2⅞ (65)
752/753 (783)	¾ (19)	8⅞ (208)	1¾ (45)	8⅞ (225)	2⅞ (73)
754/755 (784/785)	¾ (19)	9⅞ (230)	1¾ (45)	9¾ (248)	2⅞ (73)

IN (MM)

## PARTS & ACCESSORIES



**ARM754**  
Arm for 752 to 785 door closers.



**SNB1420**  
Aluminum sex nut & steel thru-bolt kit (4) for doors 1¾" (44.5 mm) thick.



**DP754**  
For parallel arm installations where the door top rail height is insufficient for direct mounting (models 754 / 755).



**715**  
Parallel arm bracket (sizes 1 & 2).



**735**  
Parallel arm bracket (sizes 3, 4 and 5).

